


# Sub-structural Testing of Large Composite Structures – a Hybrid Simulation Approach

Jacob Paamand Waldbjørn

*Postdoctoral Fellow*

*Department of Mechanical Engineering*

*Technical University of Denmark*



## Introduction and background -



### Hybrid simulation for structural assessment

#### Purpose and aim

- Cost effective alternative to full scale testing
- Substructural technique
- Experimental substructure represents e.g. crack propagation, buckling, delamination, etc.
- The remaining portion (typically the majority) exhibits predictable mechanical behavior
- Coupling through the partitioning
- In the literature named: hardware-in-the-loop  
hybrid testing  
hybrid simulation
- QS, PsD and RT hybrid simulation (HS)

#### Approach

- Apply external load  $d_g(t)$
- Acquire computed displacement  $d_1(t) - d_0(t)$
- Apply displacement at sheared boundary
- Acquire restoring force R to reveal response of emulated structure
- Apply next load-step  $d_g(t+1)$




## Introduction and background -

Single component vs. conventional hybrid simulation


### Multi-component (conventional) HS

- Originated in the late 1960's
- Several discrete components
- Simple connection in the partitioning
- Few dofs in the partitioning (e.g. damper loaded by a unidirectional actuator)
- Mature and reliable approach which enables HS within other areas



### Single-component HS

- Contains a single component
- Complex connection in the partitioning
- Infinite dofs in the partitioning (in theory)
- Complex numerical and experimental substructure (loads and geometry)




## Introduction and background -

Perspective within single-component hybrid simulation

### Expanding application areas

- larger composite structures including: wind turbine blades, ship vessels, cars, aero planes, etc.
- Wind turbine blade: laminate and structural scale testing
- Service link between laminate (idealized stress and strain states) and structural scale testing (tested with significant simplifications)
- Advanced load configurations: dynamic and static contribution





# Single component HS-

## Overall system architecture

### Overall architecture of the HS test setup

- Operating computer to handle the numerical model, operating software and enable the required communication with conditioner and external DAQ system
- Servo hydraulic system is operated through a conventional digital PID controller
- A/D and D/A converters to enable a reliable communication between the operating computer and PID controller.




## Single component HS-

Overall system architecture

### Alternative architecture of the HS test setup




- Simulation PC included to operate the numerical substructure (most commercially available)
- OpenFresco (open source code developed at UC - Berkley) to establish a communication protocol between the simulation and Test PC
- Communication to the PID controller (FT100 controller) through the 793 software on the test pc
- Couplings matrix defining the relation between the partitioning and operation of the multi-axial load train



## Outlook within single component HS- Substructural scale testing of a SSP34m wind turbine blade

### Motivation

- Investigation of cross sectional shear distortion in the max chord section when loaded in the edgewise direction
- Increase the stresses in the leading edge region
- Experimental substructure located in the root section
- The numerical substructure includes the remaining part of the SSP blade
- Also effects like the pumping/breathing behaviour in the transition zone could be investigated in this configuration





# Outlook within single component HS-

## Substructural scale testing of a SSP34m wind turbine blade

### Partitioning of the SSP34m blade

- Investigation of cross sectional shear distortion in the max chord section (critical section)
- A load introduction zone of 6m to erase the distortion induced by the load train (meaning the numerical substructure is 26m with an experimental substructure of 14m)
- Section forces in the gauge zone of the experimental substructure is equivalent to the forces obtained in the same zone in the emulated structure
- Response of the experimental substructure is evaluated in the following to numerically to verify the setup











# Outlook within single component HS-

## Substructural scale testing of a SSP34m wind turbine blade

### Numerical evaluation of the experimental substructure

- Global response of the emulated and experimental substructure




## Outlook within single component HS-

Substructural scale testing of a SSP34m wind turbine blade

### Substructural testing using single-component HS

- The numerical substructure is discretized through a FE - model
- A representative load configuration is applied the numerical substructure
- The experimental substructure is included in the model as a simple beam model with predefined mechanical properties
- To fit the response at the sheared boundary the experimental substructure is included by adjusting the mechanical properties of the beam model
- The coupling is governed through the communication loop which ensures compatibility and equilibrium at the interface





## Outlook within single component HS-

Substructural scale testing of a SSP34m wind turbine blade

### Architecture of the single-component HS




- A schematic of the experimental and numerical substructure along with the coupling between them
- A communication loop is established through LabVIEW
- Compensators are implemented (communication delay, noise, etc) to enable a high-fidelity HS



## Outlook within single component HS- Substructural scale testing of a SSP34m wind turbine blade

### Planning and construction of substructural test rig (details)

- Load train capable of inducing an in plane load configuration with 3 dofs
- Bulkhead extending 750mm into the free end of the load carrying box girder
- Pretensioned threadbars and glue to transfer the loads from the bulkhead to the load carrying box girder
- Clamped support consist of: two concrete towers and a steel plate with the dimensions (3.4x2.8x0.120m)
- Ply wood panels are installed at the trailing and leading edge in the free end of the wind turbine blade to avoid critical peeling stresses in the adhesive bond lines




## Outlook within single component HS-

Substructural scale testing of a SSP34m wind turbine blade

### Planning and construction of substructural test rig (overall setup)

- Clamped support and load train combine to form a fatigue rated test rig
- The test setup exhibits the following load and deformation capacity:
  - I. Flapwise:  $\pm 50\text{kN}$  and  $500\text{mm}$
  - II. Edgewise:  $\pm 100\text{kN}$  and  $500\text{mm}$
  - III. Moment:  $\pm 100\text{kNm}$  and  $25$  degree



# THE END

Thanks for your attention!

Any questions?